

convert_units

v. 1.8+

Christian Biscombe

17 July 2018

`convert_units` performs unit conversions, providing a command-line interface to the `Units` module that accompanies `rxntoarb` (`lib/units.rb` in the `rxntoarb` root directory). `convert_units` requires Ruby 1.9.3 or newer.

Contents

1	Invocation and command-line options	1
2	Examples	3
3	Copyright and licence	4

1 Invocation and command-line options

`convert_units` is invoked as follows:

```
convert_units [options_list] <input_string> [output_units].
```

`input_string` should consist of an optional numerical value (assumed to be 1.0 if not specified) and a list of unit abbreviations, all of which should be separated by spaces (or alternatively by the `.` or `*` characters). Any valid SI prefix (see [Table 1](#)) may immediately precede the unit name. Note the difference between, e.g., `ms-1` (per millisecond) and `m s-1` (metre per second). Exponents on units should immediately follow the unit name, optionally preceded by the `^` character. Exponents may be integers, fractions, or decimals. Use of a solidus (`/`) to indicate reciprocal units is not supported; use negative exponents instead. Accepted unit abbreviations are listed by calling `convert_units` with the `-l` flag.

The optional `output_units` should contain the units into which the input is to be converted, following the same conventions described above. If `output_units` is present then it must have the same dimensions as `input_string`. If `output_units` is omitted (or an empty string) then conversion to SI base units will be performed.

Table 1 SI prefixes.

name	prefix	factor	name	prefix	factor
yotta	Y	10 ²⁴	deci	d	10 ⁻¹
zetta	Z	10 ²¹	centi	c	10 ⁻²
exa	E	10 ¹⁸	milli	m	10 ⁻³
peta	P	10 ¹⁵	micro	μ*	10 ⁻⁶
tera	T	10 ¹²	nano	n	10 ⁻⁹
giga	G	10 ⁹	pico	p	10 ⁻¹²
mega	M	10 ⁶	femto	f	10 ⁻¹⁵
kilo	k	10 ³	atto	a	10 ⁻¹⁸
hecto	h	10 ²	zepto	z	10 ⁻²¹
deka	da	10 ¹	yocto	y	10 ⁻²⁴

* `convert_units` allows the ASCII character `u` as well as the Unicode symbols μ (U+00B5) and μ (U+03BC) to represent the micro prefix.

The optional `options_list` may include any of the following:

- `-a|--arb` Output in *arb* format, i.e. with units in square brackets before the numerical value. Implies `-d`.
- `-d|--double-precision` Output is formatted using the letter `d` for exponents (Fortran double precision copy-and-paste mode). This option is applied automatically if `input_string` contains a double precision numerical value.
- `-f|--format <format>` Output is formatted using the specified format string. Any format string recognised by Ruby's `Kernel#sprintf` method is valid.
- `-l|--list` List all recognised units and their abbreviations.
- `-M|--mol-wt <mol-wt>` Set molecular weight to be used for concentration conversions. See § 2 for examples.
- `-s|--sig-figs` Output with the same number of significant figures as the input. Overrides `-f`.
- `-t|--tdiff` Specifies that input temperatures should be interpreted as temperature differences rather than references to absolute temperatures. See § 2 for examples.
- `-v|--version` Print version information.

2 Examples

```
> convert_units 'nM'
1e-06 mol m-3
> convert_units '2.5e-3 V cm-1'
0.25 kg m A-1 s-3
> convert_units '10 atm' 'kPa'
1013.25 kPa
> convert_units '11.893 mile h-1' 'ft s-1'
17.4431 ft s-1
```

Fractional and decimal exponents:

```
> convert_units '8.34e-8 cP Da1/3 K-1 cm2 s-1' 'Pa s kDa1/3 K-1 m2 s-1'
8.34e-16 Pa s kDa1/3 K-1 m2 s-1
> convert_units '1 M0.5'
31.6228 mol0.5 m-1.5
```

arb format:

```
> convert_units -a '0.84 pmol cm-2 min-1'
[mol m-2 s-1] 1.4d-10
```

Double precision mode:

```
> convert_units '2.5d-3 V cm-1'
0.25d0 kg m A-1 s-3
> convert_units -d '2.5e-3 V cm-1'
0.25d0 kg m A-1 s-3
```

Custom output formats:

```
> convert_units -f '%.3e' '1478.5 kJ kg-1 K-1' 'BTU lb-1 °F-1'
3.531e+02 BTU lb-1 °F-1
> convert_units -f '%.3f' '1478.5 kJ kg-1 K-1' 'BTU lb-1 °F-1'
353.132 BTU lb-1 °F-1
> convert_units -f '%.3g' '1478.5 kJ kg-1 K-1' 'BTU lb-1 °F-1'
353 BTU lb-1 °F-1
```

Significant figures mode:

```
> convert_units -s '10 atm' 'kPa'
1.0e+03 kPa
```

Concentration conversions:

```
> convert_units -M '80 kDa' '375 nM' 'mg l-1'
30 mg l-1
> convert_units -M '80 kDa' '30 mg l-1' 'nM'
375 nM
```

Temperature conversions:

```
> convert_units '100 °C'
373.15 K
> convert_units -t '100 °C'
100 K
> convert_units -- '-40 °C' '°F'
-40 °F
> convert_units -t -- '-40 °C' '°F'
-72 °F
```

3 Copyright and licence

`convert_units` source code and documentation © 2017–2018 Christian Biscombe.

`convert_units` is contributed to *arb* finite volume solver (in which copyright is held by Dalton Harvie) under the same licence terms as that project. At the time of writing, *arb* is released under the terms of the GNU General Public License (version 3) as published by the Free Software Foundation.